

耐衝撃鈕

※耐衝撃に優れており、無鉛、無蛍光の商品です。 LEAD-FREE
無鉛

HDW17 HDT17 HDS17



9 10 11.5 13 mm ^{UP}

HDW173 HDT173 HDS173



9 10 11.5 mm ^{UP}

SC17 9 10 11.5 13 mm ^{UP}



01 40 43 48 09

HDW8 HDT8 HDS8



9 10 11.5 13 mm ^{UP}

HDW101 HDT101 HDS101



9 10 11.5 13 mm ^{UP}

SC105 9 10 11.5 13 mm ^{UP}



01 40 43 48 09

SC104 10 11.5 13 mm ^{UP}



01 40 43 48 09

SRS17 10 11.5 13 15 18 20 mm ^{UP}



01 02 48 03 09

SRE105 11.5 13 15 18 20 mm ^{UP}



01 48 09

OSS17 10 11.5 13 15 mm ^{UP}



WHITE TAKASE BROWN SMOKE

OSS104 10 11.5 13 15 mm ^{UP}



WHITE TAKASE BROWN SMOKE

OSS110 10 11.5 13 15 mm ^{UP}



WHITE TAKASE BROWN SMOKE

OPS133 11.5 13 15 18 20 23 mm ^{UP}



01S 09S

※色番でリング G.S.AG を指定して下さい。
※日本製リングを使用しています。

H305S 11.5 13 15 18 20 mm ^{UP}



01 09

※品番でハトメ G.S.AG を指定して下さい。
※日本製ハトメを使用しています。

OPS128 10 11.5 13 mm ^{UP}



01AG 09AG

828A



10 11.5 13 mm ^{UP}

788A



11.5 13 mm ^{UP}

844A



10 11.5 13 mm ^{UP}

OPS109



10 11.5 13 mm ^{UP}

OPS110



10 11.5 13 mm ^{UP}

OPS112



10 11.5 13 mm ^{UP}

OPS113



11.5 13 mm ^{UP}

OPS114



11.5 13 mm ^{UP}

R101 11.5 13 15 mm ^{UP}



01 48 09

R100W



10 11.5 13 15 mm ^{UP}

R100B



10 11.5 13 15 mm ^{UP}

HY181



11.5 13 15 mm ^{UP}

OP80 9 10 11.5 13 mm ^{UP}



01 40 41 42 43 46 48 28 66 06 58 08